

AMENDMENTS TO THE CLAIMS

Please amend the claims as indicated hereafter (where underlining “_” denotes additions and strikethrough “-” denotes deletions).

Claims:

1. (Original) A method comprising:
determining a power save status of a first station wherein said first station
communicates via a shared-communications channel in
accordance with a first modulation scheme; and
enabling transmission protection at a second station via said shared-
communications channel wherein said enabling is dependent on
said power save status.
2. (Original) The method of claim 1 wherein said determining comprises:
transmitting one of a Request-to-Send frame, a Data frame, and a Null
frame to said first station via said shared-communications channel
in accordance with said first modulation scheme; and
receiving one of an Acknowledgement frame and a Clear-to-Send frame
from said first station.
3. (Original) The method of claim 1 wherein said enabling comprises
broadcasting a management frame via said shared-communications channel.

4. (Original) The method of claim 3 wherein said management frame is one of:
- (i) a Beacon frame indicating that protection status is active; and
 - (ii) a Probe-Response frame indicating that protection status is active.
5. (Original) The method of claim 3 wherein said first modulation scheme is based on one of Barker modulation and Complementary Code Keying modulation.
6. (Currently Amended) A method comprising:
- receiving a first frame from a station via a shared-communications channel wherein said station communicates in accordance with a first modulation scheme; ~~and~~
- determining whether the station is in power save mode; and
- broadcasting an IEEE 802.11 Probe-Response frame via said shared-communications channel in response to said receiving;
- wherein said IEEE 802.11 Probe-Response frame indicates that protection status is active.
7. (Original) The method of claim 6 wherein said first modulation scheme is based on one of Barker modulation and Complementary Code Keying modulation.

8. (Currently Amended) A method comprising alternately enabling and disabling transmission protection at a first station that communicates via a shared-communications channel in accordance with a first modulation scheme;

wherein said first modulation scheme is undetectable to a second station that communicates via said shared-communications channel in accordance with a second modulation scheme wherein the enabling or disabling of the transmission protection is associated with a determination of whether the first station is in a power save mode; and wherein said first modulation scheme and said second modulation scheme are different from each other.

9. (Original) The method of claim 8 wherein said enabling and said disabling are periodic with respect to one of (i) frames transmitted and (ii) time.

10. (Original) The method of claim 8 wherein said enabling and said disabling are sporadic with respect to one of (i) frames transmitted and (ii) time.

11. (Original) The method of claim 8 further comprising extending transmission protection for a first interval when receiving a first frame from said second station while transmission protection is enabled, wherein said first interval is measured in one of (i) time and (ii) frames.

12. (Original) The method of claim 8 further comprising activating protection for a first interval when receiving a first frame from said second station while transmission protection is disabled, wherein said first interval is measured in one of (i) time and (ii) frames.

13. (Original) The method of claim 8 wherein said enabling comprises transmitting a first management frame via said shared-communications channel.

14. (Original) The method of claim 13 wherein said first management frame is one of:

- (i) a Beacon frame indicating that protection status is active; and
- (ii) a Probe-Response frame indicating that protection status is active.

15. (Original) The method of claim 8:
wherein said first modulation scheme is based on one of Barker
modulation and Complementary Code Keying modulation; and
wherein said second modulation scheme is based on Orthogonal
Frequency Division Multiplexing modulation.

16. (Currently amended) A method comprising:
- transmitting a first frame comprising a duration field value to a first station
- via a shared-communications channel in accordance with a first modulation scheme;
- receiving a second frame from a second station via said shared-communications channel in accordance with a second modulation scheme during a time interval defined by said duration field value;
- and
- determining whether the second station is in power save mode; and
- receiving a third frame via said shared-communications channel in accordance with said first modulation scheme after said time interval;
- wherein said first modulation scheme is undetectable to said second station; and
- wherein said first modulation scheme and said second modulation scheme are different from each other.
17. (Original) The method of claim 16:
- wherein said first modulation scheme is based on Orthogonal Frequency Division Multiplexing modulation; and
- wherein said second modulation scheme is based on one of Barker modulation and Complementary Code Keying modulation.

18. (Original) The method of claim 16 wherein said transmitting is one of (i) periodic and (ii) sporadic.

19. (Original) The method of claim 16 wherein said frame is a Clear-to-Send frame and said first station is the sender of said frame.

20. (Original) An apparatus comprising:
a processor for determining a power save status of a first station wherein said first station communicates via a shared-communications channel in accordance with a first modulation scheme; and
a transmitter for enabling transmission protection at a second station via said shared-communications channel wherein said enabling is dependent on said power save status.

21. (Original) The apparatus of claim 20 wherein said enabling comprises broadcasting a management frame via said shared-communications channel.

22. (Original) The apparatus of claim 21 wherein said management frame is one of:

- (i) a Beacon frame indicating that protection status is active; and
- (ii) a Probe-Response frame indicating that protection status is active.

23. (Original) The apparatus of claim 21 wherein said first modulation scheme is based on one of Barker modulation and Complementary Code Keying modulation.

24. (Currently Amended) An apparatus comprising:
a receiver for receiving a first frame from a station via a shared-communications channel wherein said station communicates in accordance with a first modulation scheme and for determining whether the station is in power save mode; and
a transmitter for broadcasting an IEEE 802.11 Probe-Response frame via said shared-communications channel in response to said receiving; wherein said IEEE 802.11 Probe-Response frame indicates that protection status is active.

25. (Original) The apparatus of claim 24 wherein said first modulation scheme is based on one of Barker modulation and Complementary Code Keying modulation.

26. (Currently Amended) An apparatus comprising:
- a receiver for receiving in accordance with a first modulation scheme and
- a second modulation scheme via a shared-communications channel; and
- a transmitter for alternately enabling and disabling transmission protection at a first station ~~that~~ responsive to determining that the first station is in power save mode, wherein the first station communicates via a shared-communications channel in accordance with a first modulation scheme;
- wherein said first modulation scheme is undetectable to a second station that communicates via said shared-communications channel in accordance with a second modulation scheme; and
- wherein said first modulation scheme and said second modulation scheme are different from each other.
27. (Original) The apparatus of claim 26 wherein said enabling and said disabling are periodic with respect to one of (i) frames transmitted and (ii) time.
28. (Original) The apparatus of claim 26 wherein said enabling and said disabling are sporadic with respect to one of (i) frames transmitted and (ii) time.

29. (Original) The apparatus of claim 26 further comprising extending transmission protection for a first interval when receiving a first frame from said second station while transmission protection is enabled, wherein said first interval is measured in one of (i) time and (ii) frames.

30. (Original) The apparatus of claim 26 further comprising activating protection for a first interval when receiving a first frame from said second station while transmission protection is disabled, wherein said first interval is measured in one of (i) time and (ii) frames.

31. (Original) The apparatus of claim 26 wherein said enabling comprises transmitting a first management frame via said shared-communications channel.

32. (Original) The apparatus of claim 31 wherein said first management frame is one of:

- (i) a Beacon frame indicating that protection status is active; and
- (ii) a Probe-Response frame indicating that protection status is active.

33. (Original) The apparatus of claim 26:

wherein said first modulation scheme is based on one of Barker

modulation and Complementary Code Keying modulation; and

wherein said second modulation scheme is based on Orthogonal

Frequency Division Multiplexing modulation.

34. (Currently Amended) An apparatus comprising:
- a transmitter for transmitting a first frame comprising a duration field value to a first station via a shared-communications channel in accordance with a first modulation scheme, and for determining whether the second station is in power save mode; and
- a receiver for:
- receiving a second frame from a second station via said shared-communications channel in accordance with a second modulation scheme during a time interval defined by said duration field value; and
- receiving a third frame via said shared-communications channel in accordance with said first modulation scheme after said time interval;
- wherein said first modulation scheme is undetectable to said second station; and
- wherein said first modulation scheme and said second modulation scheme are different from each other.

35. (Original) The apparatus of claim 34:
wherein said first modulation scheme is based on Orthogonal Frequency
Division Multiplexing modulation; and
wherein said second modulation scheme is based on one of Barker
modulation and Complementary Code Keying modulation.
36. (Original) The apparatus of claim 34 wherein said transmitting is one
of (i) periodic and (ii) sporadic.
37. (Original) The apparatus of claim 34 wherein said frame is a Clear-to-
Send frame and said first station is the sender of said frame.